

WARREN

MSFL Series

Heavy Duty Package Dump Body

Warren MSFL Series dump bodies are designed for mounting on heavy duty tandem and tri-axle truck chassis. They have strong "Stacked Type" under-structure for extended life. These bodies are engineered for contractors and governmental agencies for hauling sand, gravel, asphalt mix, and other materials.



Features & Benefits of Warren MSFL Series Bodies

- ASTM A1011 A-45 High Tensile Steel
- Body, cylinder, & NTEA rated hoist manufactured by Warren
- Continuous welding throughout body for additional strength
- Available in 14'-16' lengths
- Full depth rear corner post with full depth rear crossmember
- 4 x 4 x 1/8" boxed tubing top rails
- 10" wrap around front corner post
- 6" wide vertical and horizontal side braces



www.dumptrucks.com
www.spreaders.com

Warren, Inc.
707 North Fir (P.O. Box 1719)
Collins, MS 39428

Phone: 601-765-8221
Fax: 601-765-4554
Toll Free: 800-228-4842

MSFL Series Specifications

Body

Construction:	ASTM A1011 A-45 High Tensile Steel
Understructure:	4" - 5.4#/ft. channel crossmembers on 12" centers 7" - 12.5#/ft. channel longitudinals
Floor:	3/16" high tensile steel w/ radius edges
Sides:	10 ga. steel w/ 4" x 4" x 1/8" sq. tube top rail 6" wide vertical supports Horizontal side braces and 1/4" x 2" tarp rail Full depth rear corner posts and skirt 10" wrap around front corner posts Dirt shedding rub rails
Tailgate:	10 ga., 9-panel with 6" slope 6" higher than sides Offset flame cut 1 1/4" hinge and 1 1/4" latch pins Air Operated Double lower sockets w/ over hooks
Front Bulkhead:	10 ga. steel with horizontal integrally formed braces Doug house with access door
Spreader Apron:	Standard 8" weld-on
Dimensions:	Width—inside 7'3" Lengths—14' through 16'
Capacity:	Struck/sides & ends 14 - 13/15 16' - 15/17 (42" sides 48" ends) 15' - 14/16 16' - 17/19 (48" sides 56" ends)



Shown with optional tarp system

Hoists

Type:	Telescopic sub-frameless hoist
Model:	VTLW-63 Series
Pivot Pin:	1 15/16"
Mounting Height:	11"
Pivot:	12"
Cylinder:	
Barrel O.D.:	7 1/2"
Stroke:	110", 126", 135", 142"
Disp. (cu. in.):	1000, 1050
Hydraulic Pump:	Direct PTO Mount
Model:	F-35
Housing:	Cast Iron
Capacity:	35 GPM @ 1400 RPM
Controls:	Air

Distributed by:



www.dumptrucks.com
www.spreaders.com

Warren, Inc.
707 North Fir (P.O. Box 1719)
Collins, MS 39428

Phone: 601-765-8221
Fax: 601-765-4554
Toll Free: 800-228-4842